

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4962)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Россия +7(495)268-04-70

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Казахстан +7(7172)727-132

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Киргизия +996(312)96-26-47

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

<https://zetron.nt-rt.ru/> || znc@nt-rt.ru

Zerton MS104K-L-MA Portable Methyl acrylate Leakage Tester



Parameter

Detection Factor	Methyl acrylate		
Detection Range	0-10, 50, 100, 1000, 5000ppm		
Resolution	1ppm		
Sensor Type	Electrochemical sensor, IR sensor		
Sensor life	2-3 years		
Measuring method	Built-in pump suction, can be switched to diffusion, diffusion + pump suction detection mode		
Display	LCD		
Display content	Real-time concentration, unit, gas name, alarm status, time, storage status, communication status, power, charging status, etc.		
Detection accuracy	Typical precision: $\leq \pm 3\%$ FS (optional higher precision sensor)	Uncertainty	$\leq \pm 2\%$
Linearity	$\leq \pm 3\%$	Repeatability	$\leq \pm 2\%$
Response time	T90 $\leq$ 20 seconds	Recovery time	$\leq$ 30 seconds
Operating power supply	DC3.7 V*2		
Battery capacity	2500mAh rechargeable polymer battery, with over-charge, over-discharge, over-voltage, short-circuit, overheating protection function.		
Environment	Temperature: -20°C~+60°C, customizable -40°C~+70°C; Relative humidity: 10-95%RH		
Communication Interface	Standard Type-C (2 hours fully charged)		
Data storage	Standard capacity of not less than 100,000 items; support for local view, delete or data export, storage time interval arbitrary settings		
Interface language	Chinese, English and other languages can be customized		
Explosion-proof type	Intrinsically safe Exia II CT4Ga		
Protection class	IP68		
Housing material	High-strength corrosion-resistant fire-resistant polycarbonate and rubber protective cover, drop-proof wear-resistant anti-static, effective drop resistance $\geq$ 5 meters		
Dimension	Maximum size 167X64X62mm(L×W×H)		

Weight	Approx. 280g
Standard accessories	Calibration cover, pump suction nozzle, manual, certificate of conformity, USB charger (including data cable), instrument packaging color box
Optional accessories	① 0.2 meters swan neck sampling probe;
	② activated carbon filter;
	③ 0.4 meters stainless steel sampling handle (including 1 meter hose);

Zerton MS104K-L-C2H6S2 Portable Dimethyl Disulfide Gas Detector



Parameter

Detection Factor	C2H6S2 Dimethyl Disulfide		
Detection Range	0-10, 50, 100, 1000, 5000ppm		
Resolution	1ppm		
Sensor Type	EC sensor		
Sensor life	2-3 years		
Measuring method	Built-in pump suction, can be switched to diffusion, diffusion + pump suction detection mode		
Display	LCD		
Display content	Real-time concentration, unit, gas name, alarm status, time, storage status, communication status, power, charging status, etc.		
Detection accuracy	Typical precision: $\leq \pm 3\%$ FS (optional higher precision sensor)	Uncertainty	$\leq \pm 2\%$
Linearity	$\leq \pm 3\%$	Repeatability	$\leq \pm 2\%$
Response time	T90 ≤ 20 seconds	Recovery time	≤ 30 seconds
Operating power supply	DC3.7 V*2		
Battery capacity	2500mAh rechargeable polymer battery, with over-charge, over-discharge, over-voltage, short-circuit, overheating protection function.		
Environment	Temperature: $-20^{\circ}\text{C} \sim +60^{\circ}\text{C}$, customizable $-40^{\circ}\text{C} \sim +70^{\circ}\text{C}$; Relative humidity: 10-95%RH		
Communication Interface	Standard Type-C (2 hours fully charged)		
Data storage	Standard capacity of not less than 100,000 items; support for local view, delete or data export, storage time interval arbitrary settings		
Interface language	Chinese, English and other languages can be customized		
Explosion-proof type	Intrinsically safe Exia II CT4Ga		
Protection class	IP68		
Housing material	High-strength corrosion-resistant fire-resistant polycarbonate and rubber protective cover, drop-proof wear-resistant anti-static, effective drop resistance ≥ 5 meters		
Dimension	Maximum size 167X64X62mm(L×W×H)		
Weight	Approx. 280g		
Standard accessories	Calibration cover, pump suction nozzle, manual, certificate of conformity, USB charger (including data cable), instrument		

	packaging color box
Optional accessories	① 0.2 meters swan neck sampling probe;
	② activated carbon filter;
	③ 0.4 meters stainless steel sampling handle (including 1 meter hose);

Zerton MS104K-L-SiH₂Cl₂ Portable Dichlorosilane Gas Detector



Parameter

Detection Factor	SiH ₂ Cl ₂ Dichlorosilane		
Detection Range	0-10, 50, 100, 1000, 5000ppm		
Resolution	1ppm		
Sensor Type	EC sensor		
Sensor life	2-3 years		
Measuring method	Built-in pump suction, can be switched to diffusion, diffusion + pump suction detection mode		
Display	LCD		
Display content	Real-time concentration, unit, gas name, alarm status, time, storage status, communication status, power, charging status, etc.		
Detection accuracy	Typical precision: $\leq \pm 3\%$ FS (optional higher precision sensor)	Uncertainty	$\leq \pm 2\%$
Linearity	$\leq \pm 3\%$	Repeatability	$\leq \pm 2\%$
Response time	T ₉₀ ≤ 20 seconds	Recovery time	≤ 30 seconds
Operating power supply	DC3.7 V*2		
Battery capacity	2500mAh rechargeable polymer battery, with over-charge, over-discharge, over-voltage, short-circuit, overheating protection function.		
Environment	Temperature: -20°C~+60°C, customizable -40°C~+70°C; Relative humidity: 10-95%RH		
Communication Interface	Standard Type-C (2 hours fully charged)		
Data storage	Standard capacity of not less than 100,000 items; support for local view, delete or data export, storage time interval arbitrary settings		
Interface language	Chinese, English and other languages can be customized		
Explosion-proof type	Intrinsically safe Exia II CT4Ga		
Protection class	IP68		
Housing material	High-strength corrosion-resistant fire-resistant polycarbonate and rubber protective cover, drop-proof wear-resistant anti-static, effective drop resistance ≥ 5 meters		
Dimension	Maximum size 167X64X62mm(L×W×H)		
Weight	Approx. 280g		
Standard accessories	Calibration cover, pump suction nozzle, manual, certificate of conformity, USB charger (including data cable), instrument packaging color box		

Optional accessories	① 0.2 meters swan neck sampling probe;
	② activated carbon filter;
	③ 0.4 meters stainless steel sampling handle (including 1 meter hose);

Zerton MS104K-L-SiH3Cl Handheld Chlorosilane Gas detector



Parameter			
Detection Factor	SiH3Cl Chlorosilane		
Detection Range	0-10, 50, 100, 1000, 5000ppm		
Resolution	1ppm		
Sensor Type	electrochemical sensor		
Sensor life	2-3 years		
Measuring method	Built-in pump suction, can be switched to diffusion, diffusion + pump suction detection mode		
Display	LCD		
Display content	Real-time concentration, unit, gas name, alarm status, time, storage status, communication status, power, charging status, etc.		
Detection accuracy	Typical precision: $\leq \pm 3\%$ FS (optional higher precision sensor)	Uncertainty	$\leq \pm 2\%$
Linearity	$\leq \pm 3\%$	Repeatability	$\leq \pm 2\%$
Response time	T90 ≤ 20 seconds	Recovery time	≤ 30 seconds
Operating power supply	DC3.7 V*2		
Battery capacity	2500mAh rechargeable polymer battery, with over-charge, over-discharge, over-voltage, short-circuit, overheating protection function.		
Environment	Temperature: -20°C~+60°C, customizable -40°C~+70°C; Relative humidity: 10-95%RH		
Communication Interface	Standard Type-C (2 hours fully charged)		
Data storage	Standard capacity of not less than 100,000 items; support for local view, delete or data export, storage time interval arbitrary settings		
Interface language	Chinese, English and other languages can be customized		
Explosion-proof type	Intrinsically safe Exia II CT4Ga		
Protection class	IP68		
Housing material	High-strength corrosion-resistant fire-resistant polycarbonate and rubber protective cover, drop-proof wear-resistant anti-static, effective drop resistance ≥ 5 meters		
Dimension	Maximum size 167X64X62mm(L×W×H)		
Weight	Approx. 280g		
Standard accessories	Calibration cover, pump suction nozzle, manual, certificate of conformity, USB charger (including data cable), instrument packaging color box		
Optional accessories	① 0.2 meters swan neck sampling probe;		
	② activated carbon filter;		

Zerton MS104K-L-SiF4 Portable Silicon Tetrafluoride Gas Detector



Parameter

Detection Factor	SiF4 Silicon Tetrafluoride		
Detection Range	0-10, 50, 100, 1000, 5000ppm		
Resolution	1ppm		
Sensor Type	Electrochemical sensor		
Sensor life	2-3 years		
Measuring method	Built-in pump suction, can be switched to diffusion, diffusion + pump suction detection mode		
Display	LCD		
Display content	Real-time concentration, unit, gas name, alarm status, time, storage status, communication status, power, charging status, etc.		
Detection accuracy	Typical precision: $\leq \pm 3\%$ FS (optional higher precision sensor)	Uncertainty	$\leq \pm 2\%$
Linearity	$\leq \pm 3\%$	Repeatability	$\leq \pm 2\%$
Response time	T90 ≤ 20 seconds	Recovery time	≤ 30 seconds
Operating power supply	DC3.7 V*2		
Battery capacity	2500mAh rechargeable polymer battery, with over-charge, over-discharge, over-voltage, short-circuit, overheating protection function.		
Environment	Temperature: -20°C~+60°C, customizable -40°C~+70°C; Relative humidity: 10-95%RH		
Communication Interface	Standard Type-C (2 hours fully charged)		
Data storage	Standard capacity of not less than 100,000 items; support for local view, delete or data export, storage time interval arbitrary settings		
Interface language	Chinese, English and other languages can be customized		
Explosion-proof type	Intrinsically safe Exia II CT4Ga		
Protection class	IP68		
Housing material	High-strength corrosion-resistant fire-resistant polycarbonate and rubber protective cover, drop-proof wear-resistant anti-static, effective drop resistance ≥ 5 meters		
Dimension	Maximum size 167X64X62mm(L×W×H)		
Weight	Approx. 280g		
Standard accessories	Calibration cover, pump suction nozzle, manual, certificate of conformity, USB charger (including data cable), instrument packaging color box		
Optional accessories	① 0.2 meters swan neck sampling probe;		
	② activated carbon filter;		
	③ 0.4 meters stainless steel sampling handle (including 1 meter hose);		

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Россия +7(495)268-04-70

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Казахстан +7(7172)727-132

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Киргизия +996(312)96-26-47

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

<https://zetron.nt-rt.ru/> || znc@nt-rt.ru